



## AA903C WALL MASTER STATION



### GENERAL:

Loudspeaking hands-free operation.

Stainless Steel front plate.

Full keypad with access to all system features.

Sensitive electret microphone.

Volume control on front panel.

Handset connector on front panel.

Operates with Ring-Master Systems  
CB901, CB901CA, CB901EX, RM5000 and RM5000EX.

Made in USA

### DESCRIPTION:

The AA903C has speaker and microphone for normal hands free speech with a range of 3-5 meters (10-15 feet). The stations key board consists of 10 numeric dialing keys (DTMF), push-to-talk key (T), cancel key (X), volume UP/DOWN keys, privacy key (P) and a microphone mute key (M). A status LED is used for indicating station-ON and Privacy. The station offers a module plug on the face plate for easy installation of the optional handset for confidential speaking

### FEATURES:

All system features are accessed from the keypad.

Refer to documentation for features in the system used: CB901, RM5000, CB901EX or RM5000EX.

Use optional I/O Board (IF932) for output to dome light and inputs from switches.

### ORDERING INFORMATION:

<b>AA903C</b>	Wall master station
<b>GD501</b>	Handset
<b>IF932</b>	Input/Output Board (for T, 0, X, Strobe...)
<b>BBF863</b>	Flush back-box
<b>BBS863</b>	Surface back-box
<b>BBD905</b>	Desk back-box
<b>BF640A</b>	Cord, Straight 6' M8 Black
<b>BF645A</b>	Cord, Straight 1' M8 Black
<b>KB171</b>	Jack, Modular 8, Surface

## TECHNICAL DATA

### AA903C

**Operating Voltage:**

20-27 V DC

**Power Consumption:**

150 mA max.

**Dimensions (HWD):**

250mm x 140mm x 40mm  
(9.85" x 5.5" x 1.6")

**Weight:**

0.52 Kg (1.6 lb)

**Central Exchange Connections:**

Terminated in RJ45 Connector.

1 twisted pair (UTP) for audio/signaling.

1 twisted pair (UTP) for power.

**Line Specifications:**

Audio: Galvanic line,

Frequency range: 300-5000 hZ

Normal speech level: -12 dBm

Max. speech level: +4 dBm

DTMF signaling: -10 dBm



57 TRADE ZONE DRIVE  
RONKONKOMA, N.Y. 11779 USA

Tel: 1-631-585-7464

Fax: 1-631-585-7410

mail@RingComm.com

<http://www.RingComm.com>

