



AA926 WALL INDUSTRIAL MASTER STATION



GENERAL:

Weather proof enclosure

20 watt amplifier

Optional: External Talk back speaker

**Optional: Separate input speaker (microphone)
and output speaker**

Optional: Handset (GD509)

Push To Talk button

Microphone mute button

Keypad volume control

Station on lamp

Full keypad with access to all system features.

Call indication LED

External inputs: Direct Access, PTT and Cancel

External output: Strobe control relay

Operates with Ring-Master Systems CB901 and RM5000.

24V AC/DC power 1 amp max

Made in USA

DESCRIPTION:

The AA926 key board consists of 10 numeric dialing keys (DTMF), push-to-talk key (T), cancel key (X), volume UP/DOWN keys, privacy key (P) and a microphone mute key (M). A status LED is used for indicating station-ON and Privacy. The station offers a module plug on the face plate for easy installation of the optional handset for confidential speaking

FEATURES:

All system features are accessed from the keypad.

Refer to documentation for features in the system used: CB901, RM5000, RM5000CA or RM5000EX.

ORDERING INFORMATION:

AA926 Wall master station surface

GD509 Handset

306-8 Talk Back Speaker 8 ohm

TECHNICAL DATA

AA926

Operating Voltage:

20-27 V DC/ 24 V AC

Power Consumption:

1 A max.

Dimensions (HWD):

220mm x 120mm x 91mm
(8 21/32" x 4 23/32" x 3 37/64")

Weight:

0.52 Kg (1.6 lb)

Central Exchange Connections:

Terminated in RJ45 Connector.

1 twisted pair (UTP) for audio/signaling.

1 twisted pair (UTP) for power.

Line Specifications:

Audio: Galvanic line,

Frequency range: 300-5000 hZ

Normal speech level: -12 dBm

Max. speech level: +4 dBm

DTMF signaling:-10 dBm



57 TRADE ZONE DRIVE
RONKONKOMA, N.Y. 11779 USA

Tel: 1-631-585-7464

Fax: 1-631-585-7410

mail@RingComm.com

<http://www.RingComm.com>

