OO Ring-Master

EMCS-900 Emergency Call Station



GENERAL:

Stainless Steel Vandal Proof Construction (11 gauge, powder coated) Bright Safety Yellow for High Visibility Blue Location Identification Light (24Vdc) Amber Face Light for night operation (24Vdc) Bright Blue Strobe Light (24Vdc) Standard 3 gang opening for Intercom mounting Weather Resistant for indoor/outdoor use Optional: Internal CCTV Camera, External Horn, Noise (scream) detection module

DESCRIPTION:

The EMCS-900 Emergency call station is a heavy duty wall mounted intercom station with a constant on locator light. Heavy duty vandal resistant construction. Powder coated stainless steel prevents the chance of any rust. When a call is placed, a bright blue strobe will flash 60 times per minute and remain flashing until the call is answered. Once answered, two way voice communication is established. Designed for hospitals, college campuses, parking lots, shopping malls, industrial complexes, etc.

Compatible with Intercom stations (extra cost option): SS910, SS911, SS912, SS913

Compatible with Intercom Control Boards (extra cost option): Strobe, Horn, ADA and Camera, (AN913) Strobe, Horn, ADA, Camera and Scream Detection (AN912EAR) Strobe, Horn, ADA, Camera and Remote Relay control for doors and gates (AN912RR)

ORDERING INFORMATION:

EMCS-900	Emergency Call Stations
SS910	Sub Station, no buttons
SS911	Sub Station, 1 button
SS912	Sub Station, 2 button
SS913	Sub Station, 3 button
AN913	Call-in-interface
AND912EAR	Call-in-interface with sound level detection
AN912RR	Call-in-interface with remote relay

RC1123

TECHNICAL DATA EMCS-900

Operating Voltage:

24 V DC

Power Consumption: .5 A max.

Dimensions (HWD): 28 3/4" H x 10.5"W x 7.5"D

Weight:

32.0 lbs

Housing: 11 guage (.119) Stainless Steel

Lights:

High Output LED's

Strobe Lens: Lexan®

Strobe:

300K candle power



